

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B31B 1/90, B65D 83/08		A2	(11) International Publication Number: WO 96/35574
			(43) International Publication Date: 14 November 1996 (14.11.96)
(21) International Application Number: PCT/GB96/01095		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 8 May 1996 (08.05.96)			
(30) Priority Data: 9509625.1 12 May 1995 (12.05.95) GB 9521331.0 18 October 1995 (18.10.95) GB 9605375.6 14 March 1996 (14.03.96) GB			
(71) Applicant (for all designated States except US): CARTON EDGE LIMITED [GB/GB]; 213A Torrington Avenue, Coventry CV4 9HN (GB).		Published <i>Without international search report and to be republished upon receipt of that report.</i>	
(72) Inventors; and			
(75) Inventors/Applicants (for US only): OWEN, Edwin, Wyn [GB/GB]; 6 Lant Close, Tile Hill, Coventry CV4 9TG (GB). JAMIE, Ian [GB/GB]; 45 Almond Avenue, Leamington Spa, Warwickshire CV32 6QD (GB).			
(74) Agent: DEMPSTER, Benjamin, John, Naftel; Withers & Rogers, 4 Dyer's Buildings, Holborn, London EC1N 2JT (GB).			

(54) Title: AN IMPREGNATED AND SERRATED CUTTING STRIP FOR A CARTON



(57) Abstract

A serrated cutting strip (26) for a carton comprises paper or board impregnated with a mix of acrylic resin and urea formaldehyde. The strip is 0.2 to 0.5 mm in thickness and can bend without cracking over a bar of 20 mm diameter. The strip has adhesive on one side and a release sheet (28) on the adhesive. The strip is applied to a carton by apparatus (10) which comprises rollers (44, 45) for advancing a substrate sheet (24), a cutter (12), an edge (46) in front of the cutter (12) and means (44, 45) for drawing a release sheet (28) away from the edge (46).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

AN IMPREGNATED AND SERRATED CUTTING STRIP FOR A CARTON

5 The invention relates to a serrated cutting strip for a carton, the use of a material in the formation of the strip and a method and apparatus for applying a cutting strip to a carton.

10 It is known to apply a metal cutting strip to a carton for cling film so that cling film withdrawn from the carton can be cut on the metal cutting strip. The metal strip may be applied by a machine such as a Faustel D17 Edger. In the machine, metal sheet from a roll is advanced by passing between driven rollers. The sheet enters a guide comprising a shallow slot. The guide is angled downwardly at its end and directs the sheet between a block and a lower die. An upper die is movable to cut the sheet. The upper die also
20 includes pins which pass through the block and lower die to perforate the sheet before it is cut. This perforating action leaves downwardly extending teeth around each perforation. When the upper die has cut a strip from the sheet, the strip is held onto the die
25 by suction and is carried down onto a carton blank where the pressure of the upper die forces the teeth into the carton to mechanically fix the metal strip to

the carton.

The known method is relatively slow and the metal strip blunts the dies relatively quickly so that they must be re-sharpened.

According to one aspect of the invention there is provided a method of applying a cutting strip to a carton comprising advancing a substrate comprising a sheet of cutting strip material having adhesive on one side thereof and a release sheet over the adhesive, peeling away the release sheet in front of a cutter, cutting the cutting strip material into a strip with the cutter, and, bringing the adhesive carrying side of the strip into contact with the carton.

In this way, the substrate material need not be metal, but can be any suitable desired material which may, for example, be easier to cut than metal. Also, the perforation step of the known method is not required. The omission of this step and the ability to use material which is easily cut means that productivity can be greatly increased by means of the method of the invention.

Preferably, the release sheet is peeled away just in front of the cutter. This avoids the possibility of

3

the adhesive carrying side of the cutting strip material collecting dust or debris, or becoming affixed to the machine before it is cut and applied to the carton.

5

The substrate may be advanced in any suitable way and in a preferred embodiment, the substrate is advanced by pulling the part of the release sheet which has been peeled away from the cutting strip material.

10

Preferably, a light evaporation oil is applied to the cutting strip material prior to the cutting step.

This lubricates the cutting operation.

According to another aspect of the invention there is provided apparatus for carrying out the method of the first aspect of the invention.

20

According to a further aspect of the invention there is provided a Faustel D17 Edger machine having an extension on the lower wall of the feed material guide slot, the extension extending the lower wall and providing an edge for peeling at a position adjacent the path of the cutting die.

25

The normal Faustel D17 Edger machine has a guide slot which terminates too far from the path of the cutting

die to avoid sticking problems if the edge of the lower wall of the guide slot is used to peel back the release sheet. The use of an extension enables a cutting strip material with a release sheet to be used effectively.

Preferably, means is provided for applying a high evaporation oil to the feed material before it enters the machine.

10

According to another aspect of the invention there is provided apparatus for cutting and applying a cutting strip to a carton from a substrate comprising a sheet of cutting strip material having adhesive on one side thereof and a release sheet over the adhesive, the apparatus comprising means for advancing a substrate sheet, a cutter, an edge in front of the cutter and means for drawing a release sheet away from the edge.

20 Preferably, the edge is immediately in front of the cutter.

The advancing means and the drawing means may be distinct, but preferably the advancing means comprises the drawing means. The drawing means may comprise a pair of rollers.

25

5

The apparatus may be any suitable apparatus and may be a Faustel D17 Edger for example. In that case, the drawing means and advancing means preferably comprise the feed rollers of the machine.

5

The apparatus preferably further includes means for applying a high evaporation oil to a cutting strip material.

10

The cutting strip material may be of any suitable type and may comprise any impregnated paper or board and/or may comprise a mix of acrylic resin and urea formaldehyde with a structural filler such as paper or board. This gives sufficient stiffness for use as well as enabling sufficiently strong and sharp teeth to be cut onto its edge.

According to a further aspect of the invention there is provided a serrated cutting strip for a carton, the strip comprising an impregnated paper or board.

20

Preferably the strip comprises an impregnated paper. The paper or board may be impregnated with resin. The paper or board may be impregnated with one or preferably both of acrylic resin and urea formaldehyd . Further resins which may be degradable may also be impregnated. The strip preferably has

25

adhesive on one side thereof and may have a release sheet over the adhesive.

5 The cutting strip is preferably recyclable with the box which may be made of cardboard or corrugated carton material.

The impregnation may add 42.5 to 67.5% by weight of additional material.

10

According to another aspect of the invention there is provided a serrated cutting strip for a carton, the cutting strip comprising a mix of acrylic resin and urea formaldehyde with a structural filler such as paper or board.

15

The strip may comprise 60 to 70% by weight of structural filler.

20

Viewed from another aspect the invention provides the use of a material comprising a mix of acrylic resin and urea formaldehyde with a structural filler such as paper or board in the formation of a cutting strip for a carton.

25

Viewed from a further aspect the invention provides the use of a material comprising an impregnated paper

or board in the formation of a cutting strip for a carton.

5 The material may contain not less than 65% paper. The material may be 0.2 to 0.5mm in thickness, preferably 0.25 to 0.4mm thickness. The strip may be capable of bending without cracking over a bar of 20mm diameter.

10 According to yet another aspect of the invention, there is provided a cutting strip for a carton, the strip being from 0.2 to 0.5mm in thickness and being capable of bending without cracking over a bar of 20mm diameter.

This combination of strength and flexibility is particularly important and beneficial.

20 The strip may be less than 0.4mm thickness and may bend without cracking over a 12.5mm diameter bar. The strip preferably complies with Indent Test BS 6222 1988 Impact. The strip may additionally or alternatively comply with Scrape Test BS 6222 1988 3.0 N. The strip may additionally or alternatively comply with Bond Test BS 6250 Part 3 Grade 4.

25

The strip may be provided with adhesive on one side thereof and has a release sheet over the adhesive.

An embodiment of the invention will now be described by way of example and with reference to the accompanying drawing, which is a schematic side elevation of the apparatus of the embodiment.

5

The apparatus 10 is an adapted Faustel D17 Edger machine. The apparatus 10 comprises upper and lower dies 12,14, a block 16, a guide plate 18 and an extension plate 20. A roll 22 of substrate sheet material 24 is provided. The substrate sheet material 24 comprises a cutting strip material 26 which is entirely coated with adhesive on one side, the adhesive being covered by a release paper 28. The cutting strip material 26 may be a paper, acrylic resin and urea formaldehyde mix with other degradable resins. The material may include paper as a structural filler in an amount of about 65%. A suitable material is the material reference 700 SNS available from Armabord Limited in a thickness of 0.3 to 0.35mm. (Alternatives are 700 INS, 300 SNS and 300 INS)

10
15
20

25

The block 16 and guide plate 18 define a shallow horizontal slot 30 between them. At the front edge 32 of the guide plate 18, the lower surface 34 of the block 16 is angled downwardly and then continues horizontally to its front face 36. The extension

plate 32 is connected to the underside of the guide plate 18 and extends forwardly to adjacent the front face 36 of the block 16. The lower die 14 is stationary and is fixed beneath the guide plate 18 and extension 20 to leave a slot 38 therebetween. The upper die 12 is movable vertically and moves past the front face 36 of the block 16 and the end of the extension plate 20 to cut against the lower die 14. The upper die 12 includes a row of bores (not shown) which are connected to a suction pump (not shown). The upper and lower dies 12,14 have serrated cutting surfaces. An application surface 39 is provided under the upper die 12.

A trough 40 is provided in front of the entrance of the slot 30. The trough 40 includes a felt applicating pad 42 which is in communication with the interior of the trough. The trough contains a light evaporation oil such as Esso Bayol 35.

Two parallel drive rollers 44,45 are also provided in front of the slot 30. The upper roller 44 is arranged to be driven clockwise and the lower roller 45 is arranged to be driven anti-clockwise.

In use, substrate sheet 24 is withdrawn from the roll 22 and passed under the applicator pad 42 and into the

slot 30. At the front edge 46 of the extension plate 20, the release paper 28 is peeled away from the cutting strip material 26 and folded around the front edge 46 and back through the slot 38. The release paper 28 is then wound clockwise over the upper drive roller 44 and anti-clockwise over the lower roller 45. Excess cutting strip material 26 is cut off. When the machine is operated, the drive rollers 44,45 will rotate through a pre-determined angle to pull the release paper 28. As the cutting strip material 26 is sufficiently stiff in relation to the adhesive force provided by the adhesive between the release paper 28 and the cutting strip material 26, the cutting strip material will peel away from the release paper 28 at the front edge 46 of the extension plate 40 so that a portion of cutting strip material 26 protrudes from the slot 38 with its lower face carrying the adhesive. The upper die 12 is driven downwards and cuts the protruding cutting strip material 26 against the lower die 14. The cut strip is held onto the upper die 12 by the suction of the suction pump and is carried down to a carton blank waiting on the surface 29 to which it is affixed on contact by the adhesive on its lower surface. On retraction of the upper die 12, the drive rollers 44 rotate through a further angle to cause a further section of cutting strip material to extend from the slot 38 for cutting and application to a

further card blank.

The light evaporation oil from the trough 40 lubricates the cutting action of the dies 12, 14.

5

The components which have been added in comparison with a standard Faustel D17 Edger are the extension plate 20 and the trough 40. The drive rollers 44, 45 would normally receive metal sheet feed material from a roll 22 which would be driven by the rollers 44, 45 into the slot 30. The Faustel D17 Edger machine also includes pins which are mounted together with the upper die 12 and extend through bores in the block 16 and lower die 14 to perforate the metal material before it is cut and applied to a carton. These pins are removed in the adapted machine.

20

25

While a particular cutting strip material has been described, alternative materials will be apparent to the skilled man and are intended to be encompassed by this application. In particular the strip may be formed from any suitable reels of recyclable material coated on one side and in turn covered by a release paper. The strip can be any width, length and thickness that enables it to cut effectively. The strength of the strip may be controlled to pass one or more of the following tests:

12

- a) Indent Test BS 6222 1988 Impact - No damage to
surface
- b) Scrape Test BS 6222 1988 - 3.0 Newtons
- c) Flexibility (Width) 0.35mm - A 19mm Strip must
5 bend around a 12.5mm
bar but crack over a
9.5mm bar
0.4 & 0.45mm - Must bend over a bar
20.0mm
- 10 d) Bond Test BS 6250 Part 3 - Grade 4

The material thus allows a tooth sharpness sufficient
to penetrate the film to be cut. The strip may be
printed upon.

CLAIMS

1. A serrated cutting strip for a carton, the strip comprising an impregnated paper or board.

5

2. A cutting strip as claimed in claim 1, wherein the paper or board is impregnated with resin.

10

3. A cutting strip as claimed in claim 2, wherein the paper or board is impregnated with acrylic resin.

4. A cutting strip as claimed in claim 1, 2 or 3, wherein the paper or board is impregnated with urea formaldehyde.

5. A cutting strip as claimed in any preceding claim, wherein the paper or board is impregnated with at least one degradable resin.

20

6. A cutting strip as claimed in any preceding claim, wherein the impregnation adds 42.5 to 67.5% by weight of additional material.

25

7. A cutting strip as claimed in any preceding claim, wherein the strip comprises impregnated paper.

8. A serrated cutting strip for a carton, the cutting strip comprising a mix of acrylic resin and urea formaldehyde with a structural filler.

5 9. A cutting strip or the use of material as claimed in claim 8, wherein the mix further comprises at least one degradable resin.

10 10. A cutting strip as claimed in claim 8 or claim 9, wherein the strip comprises 60 to 70% by weight of structural filler.

11. A cutting strip as claimed in claim 8, 9 or 10, wherein the structural filler is paper.

15

12. The use of a material comprising an impregnated paper or board in the formation of a cutting strip for a carton.

20 13. The use of a material as claimed in claim 12, wherein the paper or board is impregnated with resin.

25 14. The use of a material as claimed in claim 13, wherein the paper or board is impregnated with acrylic resin.

15

15. The use of a material as claimed in claim 12, 13 or 14, wherein the paper or board is impregnated with urea formaldehyde.

5 16. The use of a material as claimed in any of claims 12 to 15, wherein the paper or board is impregnated with at least one degradable resin.

10 17. The use of a material as claimed in any of claims 12 to 16, wherein the impregnation adds 42.5 to 67.5% by weight of additional material.

15 18. The use of a material as claimed in any of claims 12 to 17, wherein the strip comprises impregnated paper.

20 19. The use of a material comprising a mix of acrylic resin and urea formaldehyde with a structural filler in the formation of a cutting strip for a carton.

25 20. The use of a material as claimed in claim 19, wherein the mix further comprises at least one degradable resin.

21. The use of a material as claimed in claim 19 or 20, wherein the strip comprises 60 to 70% by weight

of structural filler.

22. The use of a material as claimed in claim 19, 20 or 21, wherein the structural filler is paper.

5

23. A cutting strip as claimed in any of claims 1 to 11, wherein the strip is from 0.2 to 0.5mm in thickness.

10

24. A cutting strip as claimed in claim 23, wherein the strip is capable of bending without cracking over a bar of 20mm diameter.

15

25. A cutting strip for a carton, the strip being from 0.2 to 0.5mm in thickness and being capable of bending without cracking over a bar of 20mm diameter.

20

26. A cutting strip as claimed in claim 23, 24 or 25, wherein the strip is less than 0.4mm thickness and will bend without cracking over a 12.5mm diameter bar.

25

27. A cutting strip for a carton as claimed in any of claims 23 to 26, wherein the strip complies with Indent Test BS 6222 1988 Impact.

28. A cutting strip for a carton as claimed in any of claims 23 to 27, wherein the strip complies with Scrape Test BS 6222 1986 3.0 N.

5 29. A cutting strip for a carton as claimed in any of claims 23 to 28, wherein the strip complies with Bond Test BS 6250 Part 3 Grade 4.

10 30. A cutting strip as claimed any of claims 1 to 11 and 23 to 29, wherein the strip has adhesive on one side thereof and has a release sheet over the adhesive.

31. A method of applying a cutting strip to a carton comprising advancing a substrate comprising a sheet of cutting strip material having adhesive on one side thereof and a release sheet over the adhesive, peeling away the release sheet in front of a cutter, cutting the cutting strip material into a strip with the cutter, and, bringing the adhesive carrying side of the strip into contact with the carton.

32. A method as claimed in claim 31, wherein the release sheet is peeled away just in front of the cutter.

33. A method as claimed in claim 31 or claim 32,

wherein the substrate is advanced by pulling the part of the release sheet which has been peeled away from the cutting strip material.

5 34. A method as claimed in claim 31, 32 or 33, wherein a light evaporation oil is applied to the cutting strip material prior to the cutting step.

10 35. Apparatus for carrying out the method of any of claims 31 to 34.

15 36. A Faustel D17 Edger machine having an extension on the lower wall of the feed material guide slot, the extension extending the lower wall and providing an edge for peeling at a position adjacent the path of the cutting die.

20 37. A machine as claimed in claim 36, wherein means is provided for applying a high evaporation oil to the feed material before it enters the machine.

25 38. Apparatus for cutting and applying a cutting strip to a carton from a substrate comprising a sheet of cutting strip material having adhesive on one side thereof and a release sheet over the adhesive, the apparatus comprising means for advancing a substrate sheet, a cutter, an edge in front of the cutter and

means for drawing a release sheet away from the edge.

39. Apparatus as claimed in claim 38, wherein the edge is immediately in front of the cutter.

5

40. Apparatus as claimed in claim 38 or claim 39, wherein the advancing means comprises the drawing means.

10

41. Apparatus as claimed in claim 38, 39 or 40, wherein the drawing means comprises a pair of rollers.

42. Apparatus as claimed in any of claims 38 to 41, wherein the apparatus is a Faustel D17 Edger.

43. Apparatus as claimed in claim 42, wherein the drawing means and advancing means comprise the feed rollers of the machine.

20

44. Apparatus as claimed in any of claims 38 to 43, wherein the apparatus further includes means for applying a high evaporation oil to a cutting strip material.

1/1





FIG. 1.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B31B 1/90, B65D 83/08, B65H 35/00		A3	(11) International Publication Number: WO 96/35574
			(43) International Publication Date: 14 November 1996 (14.11.96)
(21) International Application Number: PCT/GB96/01095		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 8 May 1996 (08.05.96)			
(30) Priority Data:			
9509625.1	12 May 1995 (12.05.95)	GB	
9521331.0	18 October 1995 (18.10.95)	GB	
9605375.6	14 March 1996 (14.03.96)	GB	
(71) Applicant (for all designated States except US): CARTON EDGE LIMITED [GB/GB]; 213A Torrington Avenue, Coventry CV4 9HN (GB).		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(72) Inventors; and			
(75) Inventors/Applicants (for US only): OWEN, Edwin, Wyn [GB/GB]; 6 Lant Close, Tile Hill, Coventry CV4 9TG (GB). JAMIE, Ian [GB/GB]; 45 Almond Avenue, Leamington Spa, Warwickshire CV32 6QD (GB).		(88) Date of publication of the international search report: 9 January 1997 (09.01.97)	
(74) Agent: DEMPSTER, Benjamin, John, Naftel; Withers & Rogers, 4 Dyer's Buildings, Holborn, London EC1N 2JT (GB).			

(54) Title: AN IMPREGNATED AND SERRATED CUTTING STRIP FOR A CARTON



(57) Abstract

A serrated cutting strip (26) for a carton comprises paper or board impregnated with a mix of acrylic resin and urea formaldehyde. The strip is 0.2 to 0.5 mm in thickness and can bend without cracking over a bar of 20 mm diameter. The strip has adhesive on one side and a release sheet (28) on the adhesive. The strip is applied to a carton by apparatus (10) which comprises rollers (44, 45) for advancing a substrate sheet (24), a cutter (12), an edge (46) in front of the cutter (12) and means (44, 45) for drawing a release sheet (28) away from the edge (46).

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/GB 96/01095

A. CLASSIFICATION F SUBJECT MATTER
IPC 6 B31B1/90 B65D83/08 B65H35/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B31B B65D B65H B32B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 135 784 A (OKUMURA EITARO) 4 August 1992 see the whole document ---	1-3,7, 12-14,18
X	GB 1 528 040 A (INT PAPER CO) 11 October 1978 see claim 16 ---	1,23
X	NL 295 768 A (GENERAL FOODS CORP.) 10 May 1965 see page 5, paragraph 2 ---	1
X	NL 6 900 686 A (N.V. LEEUWARDER PAPIERWARENFABRIEK) 17 July 1970 see the whole document ---	1
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

21 November 1996

Date of mailing of the international search report

02.12.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Pipping, L

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/GB 96/01095

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 017, no. 569 (M-1496), 15 October 1993 & JP 05 162743 A (TOKYO AUTOM MACH WORKS LTD), 29 June 1993, see abstract; figure 2 ---	31-43
A	US 3 986 440 A (MACDONALD WILLIAM ET AL) 19 October 1976 ---	31
A	EP 0 126 833 A (AKTINO PLAST AB) 5 December 1984 see page 5, line 23 - line 30 -----	33

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB 96/ 01095

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

- 1.- Claims 1-24, 26-30 when dependant on claim 1-24: A serrated cutting strip for a carton and its use comprising an impregnated paper or board.
- 2.- Claims 25-30: A cutting strip for a carton 0,2-0,5 mm thick and flexible.
- 3.- Claims 31-44: A method and apparatus for applying a cutting strip to a carton, the cutting strip having an adhesive and backing paper.

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☒ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:

1-24, 26-30 (when dependant on claims 1-24), 31-44
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest.

☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. l. Application No
PCT/GB 96/01095

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-5135784	04-08-92	NONE	
GB-A-1528040	11-10-78	CA-A- 1041817	07-11-78
		AU-B- 507896	28-02-80
		AU-A- 1990276	01-06-78
		BE-A- 848657	23-05-77
		DE-A- 2559292	02-06-77
		FR-A- 2332218	17-06-77
		LU-A- 76255	13-12-77
		NL-A- 7612861	26-05-77
NL-A-295768		NONE	
NL-A-6900686	17-07-70	BE-A- 744399	14-07-70
		DE-A- 2001031	23-07-70
		FR-A- 2028372	09-10-70
US-A-3986440	19-10-76	NONE	
EP-A-0126833	05-12-84	NONE	